

ZSST Shrink-N-Shield ®

Tough, thin wall, heat shrinkable polyolefine jacket
(UL-Registration) enclosing flexible, metallized conductive cloth shield

Available in 6 sizes: 4, 7, 10, 12, 20, 25 mm
Delivered in 1,2 m lengths.



Standard Größen

Teil-Nr.	VOR DEM SCHRUMPFEN		NACH DEM SCHRUMPFEN	
	A Innen Ø in mm	B Innen Ø in mm	C Wandstärke in mm	
ZSST-4	4,57	2,29	0,51	
ZSST-7	6,15	3,07	0,64	
ZSST-10	9,32	4,66	0,64	
ZSST-12	12,49	6,25	0,64	
ZSST-20	18,85	9,43	0,76	
ZSST-25	25,19	12,60	0,89	

Material

polyolefine jacket enclosing metallized
conductive cloth shield

Construction

-

Closing Systems

-

Locking strength (only Z & D-track)

-

Color(s)

anthracite black

Wall thickness (mm) ± 10%

after shrinkage 0.5 - 0.9 mm acc. to diameter

UL-Registration

UL 224

Temperature range

- 40°C / +125°C

Self-extinguishing

yes

UV-resistant

yes

Ozone resistant

yes

Weather resistant

yes

Dielectric strength (DIN 53481)

DIN

Hardness: tubing / track

-